

Suitable for house garden.

250W motor

25L tank

Integrated type

5 levels pressure



MS-252RT25



■ Nozzle (MS-252RT25/252R)



(MS-252CL)



4m Direct Spray

Easy carry. Integrated type.

Nozzle connection screw type G 1/4



4m Direct Spray

With reel

MS-252R

250W motor 5 levels pressure

Easy carry.



Tank and carry integrated

MS-252R + TK-50N



Case

MS-252CL

250W motor 5 levels pressure



■ Specification

Model		MS-252RT25* (With 25L Tank, carry)	MS-252R* (With reel)	MS-252CL* (With case)
PUMP	Pump Type	Single Piston		
	Max. Suction Volume	50 Hz: 3.2 L/min 60Hz: 4.0 L/min		
	Spray Volume	50Hz	2.2 L/min (spray) ~ 2.5 L/min (shot)	
		60Hz	2.7 L/min (spray) ~ 2.9 L/min (shot)	
	Max. Pressure (at Closing)	3.5 MPa (35 kgf/cm ²)		
Nozzle		Spray•Shot Adjustable		
Delivery Hose		Φ 6 x 20 M (with Reel)		Φ 6 x 20 M
MOTOR	Motor Type	Single Phase Motor		
	Voltage	AC100 V		
	Frequency	50 / 60 Hz		
	Power Consumption	50 Hz : 350 W 60 Hz : 370 W		
	Output	250 W		
	Max. Current	50 Hz :6.1 A 60 Hz : 5.3 A		
	Insulation Type	Type E		
	Breaker / Fuse	8 A (Manual)		
Power Cord		5 M		
Accessories		1 Strainer, 1 Suction Hose Φ 10 x 2.5 M, 1 Remaining Water Hose Φ 7 x 2.5 M, 1 Delivery Hose Φ 6 x 20 M		
Net Weight		23.5 kg (52 lbs)	15.5 kg (34 lbs)	9.5 kg (21 lbs)
Gross Weight		28 kg (62 lbs)	19.0 kg (42 lbs)	15 kg (33 lbs)
Dimensions LxWxH (mm)		645 x 480 x 610	585 x 370 x 440	300 x 430 x 261
Packing Unit		1		

*Japanese Domestic Model