

"Mister AUTO" Manual Pressure Sprayer

- "One hand operation lever" Easy operation designed for spraying continuously or intermittently.
- · 2-stage extendable nozzle 630 - 1135 mm.
- · Safety valve with simple pressure gauge.
- · Big funnel for easy pouring.





Double Piston Method Thin Thick piston piston Powerful! Light! **Switchable Nozzle** 1 Head 2 Heads



■ Specification

Model	HS-503W*	HS-707W*	HS-401E*
Tank Capacity	5 L	7 L	4 L
Hose Length	5 m (16 ft)		2 m (6.5 ft)
Nozzle Type	2-Stage Extendable 2-Head	4-Stage Extendable 2-Head	1-Head Nozzle
Total Extendable Length	63 - 113.5 cm (24" - 44")	63 - 201 cm (24" - 79")	38 cm (15")
Operating Pressure Around Safety Valve	0.4 MPa (4 kgf/cm²)		0.2 MPa (2 kgf/cm ²)
Spray Area	56 - 72.7 m ²	79 – 99 m²	46 – 59 m ²
Net Weight	2.7 kg (5.9 lbs) (1 unit)	2.8 kg (6.17 lbs) (1 unit)	0.96 kg (2.1 lbs) (1 unit)
Gross Weight	13.4 kg (29.5 lbs) (4 units)	14.8 kg (32.6 lbs) (4 units)	8.5 kg (18.7 lbs) (4 units)
Dimensions L×W×H (mm)	441 × 441 × 653	411 × 411 × 653	610 × 410 × 410
Packing Unit	4		6

^{*}Japanese Domestic Model

"Garden Master" Powered by **Dry Cell Battery**

- · Big tank opening for easy cleaning and refilling.
- · Internally sloped bottom design ensures all liquids are used up.











GT-3S GT-3HS ■ Specification

Model	GT-2S*	GT-3S*	GT-5S*	GT-3HS*	GT-5HS*
Tank Capacity	2 L	3 L	5 L	3 L	5 L
Hose Length	1 m (3.3 ft)	1.5 m (5 ft)		1.7 m (5.6 ft)	
Nozzle Type	1-Stage, 1-Head	3-Stage Extendable, 1-Head		3-Stage Extendable, 1-Head	1-Stage 1-Head, + Extensional
Total Extendable Length	42 cm (16")	43 - 100 cm (16" - 39")		37 - 96 cm (14" - 38")	59 - 96 cm (23" - 38")
Battery		DC 1.5 V × 4 pcs		DC 1.5 V × 6 pcs	
Rating Voltage		4.8 V		7.2 V	
Battery Life	Approx. 20 L (5.3 USG) (Alkaline Battery)) (Alkaline Battery)) (Manganese Battery)		I USG) (Alkaline Battery) I USG) (Alkaline Battery)
Spray Volume	Approx. 240 ml/min (Shower Spray) Approx. 400 ml/min (Sharp Spray)	Approx. 240 ml/min (Shower Spray) Approx. 400 ml/min (Sharp Spray)		1 Head: 450 ml/min (Shower Spray), 570 ml/min (Sharp Spray) 2 Head: 680 ml/min (Shower Spray), 740 ml/min (Sharp Spray)	
Shower Spraying Time (Full Tank)	9 min	13 min	21 min	1 Head: 8 min, 2 Head: 5 min	1 Head: 13 min, 2 Head: 8 min
Spray Angle	60 °				
Jet Distance	4 m (13 ft)		1 Head: 6.5 m,	2 Head: 4.5 m	
Standard Accessories	Measurement Cup	asurement Cup 1 Spout			
Net Weight	0.62 kg (1.3 lbs) (1 unit)	1.2 kg (2.6 lbs) (1 unit)	1.4 kg (3.8 lbs) (1 unit)	1.3 kg (2.8 lbs) (1 unit)	1.5 kg (3.3 lbs) (1 unit)
Gross Weight	3.8 kg (8.4 lbs) (4 units)	8 kg (17.6 lbs) (4 units)	4.5 kg (9.9 lbs) (2 units)	4.4 kg (9.7 lbs) (2 units)	5.1 kg (11.2 lbs) (2 units)
Dimensions LxWxH (mm)	320 × 320 × 360	540 × 385 × 375	400 × 270 × 375	405 × 385 × 310	405 × 385 × 355
Packing Unit	4	1		2	

^{*}Japanese Domestic Model

Spreader for Fertilizer

Manual type Both sowing widely and lineally are adjustable widely lineally

■ Specification

Model	HD-20
Capacity	20 L
Net Weight	1.9 kg (4.1 lbs)(1 unit)
Gross Weight	8.8 kg (19.4 lbs)(3 units)
Dimensions L×W×H(mm)	380 × 160 × 570
Packing Unit	3

Granule Applicator



■ Specification

Model	HD-8
Tank Capacity	8 L
Spraying width	$5\sim7~\mathrm{m}$
Net Weight	1.9 kg (4.1 lbs)
Gross Weight	2.8 kg (6.1 lbs)
Dimensions LxWxH (mm)	470 × 300 × 280
Packing Unit	1

Manual Granule Applicator for Fertilizer



Specification

■ Specification		
Model	HD-5	
Tank Capacity	4.6 L	
Spraying amount	400 g/min	
adjusting shutter full open		
Net Weight*	2.5 kg (5.5 lbs)	
Gross Weight	3.0 kg (6.6 lbs)	
Dimensions L×W×H (mm)	$300 \times 270 \times 370$	
Packing Unit	1	

*Bellows pipe, extension pipe and nozzle attached