




GENERATOR

Standard Generator

- High Fuel Efficiency
- Ultimate Durability
 - 100% Copper Wire for Alternator
 - Anti-Rusty fuel tank
 - Full roll cage for ultimate protection
- Less Vibration & Quiet Operation
- All models have oil alert function.



Specification

Model		GV-3000	GV-7000S	GV-3200	GV-7600S
GENERATOR	Phase	Single			
	Voltage Regulation	AVR			
	Rated Output	2 kVA	5 kVA	2.3 kVA	5.5 kVA
	Maximum Output	2.2 kVA	5.5 kVA	2.5 kVA	6 kVA
	AC Rated Frequency	50 Hz		60 Hz	
	Rated Voltage	220 V			
	Rated Ampere	9.1A	22.7 A	10.5 A	25 A
	DC Output	12 V/8.3 A			
	Continuous Running Time (rated load)	9.5 h	7.5 h	6.3 h	5 h
	Tank Capacity	12.6 L	22.6 L	12.6 L	22.6 L
Receptacle	 	 	  BS1363, 2pcs    CEE 7/4, 2pcs	  BS1363, 2pcs    CEE 7/4 NEMA L6-30	
	European socket, CEE 7/4, 2pcs	European socket, CEE 7/4, 1pc NEMA L6-30 Socket, 1pc			
ENGINE	Model	Koshin K210	Koshin K420	Koshin K210	Koshin K420
	Type	Air-cooled, 4-stroke, OHV, single cylinder			
	Displacement	212 cc	420 cc	212 cc	420 cc
	Oil Alert System	Standard			
	Starting system	Recoil	Recoil/Electric starter	Recoil	Recoil/Electric starter
	Battery	—	Maintenance-free type	—	Maintenance-free type
	Wheel Kit	—	Standard	—	Standard
	Net Weight	42.1 kg (93 lbs)	85 kg (187 lbs)	42.6 kg (94 lbs)	85 kg (187 lbs)
	Gross Weight	44 kg (97 lbs)	87 kg (192 lbs)	45 kg (99 lbs)	87 kg (192 lbs)
	Dimensions L×W×H (mm)	635 × 460 × 475	700 × 550 × 560	635 × 460 × 475	700 × 550 × 560
Packing Unit	1				

*GV-7000S/GV-7600S without battery