

POLYETHYLENE PUMP BODY

For Seawater, Fertilizer

- Superior material used.
 - PET (Polyethylene Terephthalate) for pump casing, impeller and volute casing.
 - EPDM and carbon ceramic for mechanical seal.
 - SUS for all bolts and washers.
- Powered by strong and durable engine.



PGH-50

Specifications

Model	PGH-50	
PUMP	Connection Dia	50 mm (2")
	Connection Thread	Inner Pipe Thread BSP
	Total Head	26 m (85 ft)
	Max. Suction Lift	8 m (26 ft)
	Delivery Volume	560 L/min (148 USG/min)
Material for Mechanical Seal		Ceramic Carbon
ENGINE	Type	Forced Air-cooled 4-stroke Gasoline
	Model	Honda GX120
	Exhaust Volume	118 cc
	Rated Output	2.1 kW (2.9 PS) / 3600 rpm
	Max. Output	2.6 kW (3.5 PS) / 3600 rpm
	Fuel	Automotive Unleaded Gasoline
	Fuel Tank Capacity	2.5 L (0.66 USG)
	Continuous Operating Time	Approx. 2 hrs
	Starting Method	Recoil Starter
	Standard Accessories	1 Strainer, 3 Hose Nipples, 1 Elbow 2 Hose Couplings, 3 Hose Bands, 1 Engine Tool Set
Net Weight	19.8 kg (43 lbs)	
Gross Weight	22 kg (46.3 lbs)	
Dimensions LxWxH (mm)	510 x 418 x 433	
Packing Unit	1	

Performance Curve

