

"NEW BILGE KING" Necessities for Boat

- Auto-stop feature prevents dry running, increases pump performance and life.
- Easy to use starter switch. Integrated fuse and switch assembly for ease of maintenance. Separate switch can be attached anywhere you want.
- Strainer and switch are made of a special sea water and oil resistance resin for longer durability.
- Two stage system of axial flow vane and spiral vane
- Easy to clean strainer.

■ Applications

- Draining of water and oil/water mix from bilge



BK-12



Standard Accessories

Type S Pump for without Accessories For Replacement "BILGE PUMP"




BK-12S

How to Attach Pump

Attach pump at 45 degree angle to set suction mouth and delivery mouth face upper side with 4 screws ($\phi 5 \times 10$). (See the picture below)

In a dry place, attach pump to the side of boat about 50 to 70 cm away from the bottom of the boat.

Choose the location to set the pump by considering the length of battery and starting switch cable (3 m).



■ Specifications

Model	BK-12	BK-12S	BK-24	BK-24S
Suction / Delivery Dia	15 mm (1/2")			
Max. Delivery Volume	20 L/min (5 USG/min)			
Voltage	DC 12 V		DC 24 V	
Rated Current	10 A		5 A	
Suction Lift	1 m (3 ft)			
Suction Time	2 - 5 sec (20 °C)			
Rating	80 W		90 W	
Standard Accessories (*Type S : Not Included)	1 Code with Starting Switch, 4 Tapping Screws (5x10), 4 Tapping Screws (4x16), 1 Fuse (15 A)	1 Strainer, 4 Tapping Screws (4x20), 1 Water Proofing Connector (Only S Type)	1 Delivery Nozzle, 4 Tapping Screws (4x10), 1 Fuse (8 A)	1 Delivery Nozzle Nat, 1 Hose (3 m)
Net Weight	3.6 kg (7.9 lbs)	2.3 kg (5.1 lbs)	3.6 kg (7.9 lbs)	2.3 kg (5.1 lbs)
Gross Weight	18.5 kg (41 lbs)	10 kg (22 lbs)	18.5 kg (41 lbs)	10 kg (22 lbs)
Dimensions LxWxH (mm)	485 x 323 x 346	330 x 296 x 250	485 x 323 x 346	330 x 296 x 250
Packing Unit	4			

*BK-12S, BK24S is pump for replacement.